

Part No. 36926

# 1M MINI DISPLAYPORT TO HDMI 10.2G CABLE

CONNECT MINI DISPLAYPORT DEVICES TO AN HDMI DISPLAY



## DESCRIPTION

- Connects a Mini DisplayPort equipped device to a 4K UHD HDMI display or projector
- Supports resolutions up to 3840x2160@30Hz
- Supports video mirroring and extended desktop modes
- Audio pass-through if supported by the video source
- 2 year warranty

The Lindy Mini DisplayPort to HDMI Cable is ideal for connecting a Mini DisplayPort equipped source such as a PC or laptop to an HDMI display. Supporting 4K UHD resolutions up to 3840x2160@30Hz, this cable is ideal for ensuring video is displayed in superior clarity. This cable can also be used to add another display to extend the available desktop workspace and increase productivity, great for use in residential or workplace office setups.

The Mini DisplayPort to HDMI Cable supports uncompressed 7.1 Audio and compressed Audio such as DTS-HD Master Audio, Dolby TrueHD. Please note that audio output over HDMI is only supported when the graphics card of the laptop or desktop computer supports audio output over DisplayPort.

## RELATED PRODUCTS

# 1M MINI DISPLAYPORT TO HDMI 10.2G CABLE

## CONNECTORS

<b>Connector A</b>	Mini DisplayPort Male
<b>Connector B</b>	HDMI Type A Male
<b>Housing Material</b>	Mini DisplayPort: PVCHDMI: PVC
<b>Connector Plating</b>	Gold plated
<b>Pin Construction</b>	Copper
<b>Pin Plating</b>	Gold plated
<b>Dimensions (approx.) WxDxH</b>	Mini DisplayPort: 17.8x10.8x7.9mm (0.7x0.43x0.31in) HDMI: 37.5x20.5x10.5mm (1.48x0.81x0.41in)

## SPECIFICATONS

Supported Bandwidth	10.2Gbps
Maximum Resolution	3840x2160@30Hz 4:4:4 8bit
Nominal Attenuation	100MHz-450MHz 2.44-5.09dB 450MHz-8100MHz 5.094-32.906dB
Minimum Bend Radius	50mm (1.97in)
Operating Temperature	0°C - 45°C (32°F - 113°F)
Storage Temperature	-10°C - 80°C (14°F - 176°F)

## PURCHASING INFORMATION

No.	36926
EAN	4002888369268

## CABLE CONSTRUCTION

Length	1m (3.28ft)
Standard	HDMI 1.4 DisplayPort 1.2
Colour	Black
Type	Round
Jacket Diameter	4.8mm (0.19in)
Jacket Material	PVC
Conductor Material	Tinned Copper
Conductor Gauge	32AWG
Shielding	Aluminium Braid 85%

## MISCELLANEOUS

Packaging Type	Polybag
Warranty (Years)	2
Certificated	CE, UKCA, FCC, RCM, RoHS, REACH, UL & California Proposition 65

## AVAILABLE IN OTHER LENGTHS

36925 - 0.5m (1.64ft)
36926 - 1m (3.28ft)
36927 - 2m (6.56ft)
36928 - 3m (9.84ft)
36929 - 5m (16.44ft)