

Part No 43155

5M USB 3.0 ACTIVE EXTENSION

5M USB 3.0 EXTENSION OF A USB TYPE A PORT OF YOUR COMPUTER



DESCRIPTION

- 5 metre USB 3.0 Active Extension Repeater Lead
- Supports transfer rates up to 5Gbps
- For even greater distances simply connect 2 cables in series
- Plug & Play
- 2 year warranty

The Lindy USB 3.0 Active Extension Cable uses built-in active electronics to extend the cable length of a USB 3.0 device by an additional 5m whilst continuing to support data transfer rates of up to 5Gbps. With its USB A male and USB A female connector it allows Type A devices such as storage devices, webcams and other Type A devices to be connected at longer distances to PCs, laptops and tablets, while also ensuring flexible positioning. Up to 2 extension cables can be chained together.

The Lindy USB 3.0 Active Extension Cable is compatible with all USB Type A equipped computers. It is certified by Google to provide a long distance active connection between the ASUS Chromebox and USB camera in a Google Hangouts Meet hardware installation, perfect for use in boardrooms and other video conferencing scenarios.

RELATED PRODUCTS

N/A

5M USB 3.0 ACTIVE EXTENSION

CONNECTORS

Connector A	USB Type A Male
Connector B	USB Type A Female
Power	-
Housing Material	Plastic
Connector Plating	Gold 3µ
Pin Construction	Brass
Pin Plating	Gold 15µ
Dimensions (approx.) WxDxH	USB A Male: 16x48x6mm (0.63x1.89x0.24in) USB A Female: 24x46x12mm (0.94x1.81x0.47in)

SPECIFICATONS

Supported Bandwidth	5 Gbps
Nominal Attenuation	1.5dB/2M@0.1GHz 5.0dB/2M@1.25GHz 7.5dB/2M@2.5GHz 25dB/2M@7.5GHz

Minimum Bend Radius	55mm (2.17in)
Maximum Tensile Load	1500PSI min
Operating Temperature	0°C - 60°C (32°F - 140°F)
Storage Temperature	0°C - 70°C (32°F - 158°F)
Transmission Medium	Twisted Pair
Transmission Technology	USB 3.1 Gen 1 / 3.0

PURCHASING INFORMATION

No.	43155
EAN	4002888431552

CABLE CONSTRUCTION

Length	5m (16.4ft)
Standard	USB 3.1 Gen 1 / 3.0
Colour	Black
Type	Round
Jacket Diameter	5.5mm (0.22in)
Jacket Material	Matt PVC
Conductor Material	Tinned Copper
Conductor Gauge	28AWG+24AWG
Shielding	AL Mylar

MISCELLANEOUS

Packaging Type	Blister
Packaging Dimensions	237x138x60mm (9.33x5.43x2.36in)
Net Weight	0.22kg (0.49lb)
Gross Weight	0.289kg (0.52lb)
Warranty (Years)	2
Certificated	CE, UKCA , FCC, RCM , RoHS & REACH

AVAILABLE IN OTHER LENGTHS

43155 - 5m (16.4in)

THIS PRODUCT IS ALSO AVAILABLE IN OTHER LENGTHS

43155 - 5m (16.4in)